

Safety, security and peace of mind in one neat package



No wires - No fuss, just plug and play.

View live colour video pictures of all callers before opening your door to strangers. The new Vu-Com Series 2 can stream video films or take snapshots of all callers if you are out or at home.

- Portable Handsets, can be desk/table mount or wall mounted
- Choice of 3 different models
- Remotely unlock doors
- Surveillance mode
- Recording with Mini SD card
- Built-in infrared lighting for night vision
- 12 Selectable Ringtones
- Free field range of 300 meters
- Easy to install - simple to use



The Vu-Com Series 2 system comprises a stylish weatherproof call station with simple plug in power supply plus a modern portable handset with wall or freestanding docking station/cradle and plug in charger

VC1

External call stations

- Operating frequency: 2402-2483, 5MHz
- Transmitting power: 16-20dBm
- Camera: 1/4 COMS
- Power adapter: DC5V/A
- Operating current: 300mA
- Standby current 20-30mA
- Size: 175 x 110 x 60mm
- N.W: 310g

Indoor Monitor

- Operating current: 250mA
- Screen: 2.4 inch TFT-LCD
- Sensitivity: -90dBm
- Battery capacity: 1350mah
- Standby current: 20-30mA/3.7V
- Standby time: 120 hours
- Size: 100 x 65 x 20mm
- N.W: 130g



2.4 inch TFT-LCD screen

VC2

External call stations

- Operating frequency: 2402-2483, 5MHz
- Transmitting power: 16-20dBm
- Camera: 1/4 COMS
- Power adapter: 300mA.
- Standby current 20-30mA
- Size: 175 x 105 x 60mm
- N.W: 310g

Indoor Monitor

- Operating current: 250mA
- Screen: 3.5 inch TFT-LCD
- Sensitivity: -90dBm
- Battery capacity: 1350mah
- Standby current: 20-30mA/3.7V
- Standby time: 120 hours
- Size: 140 x 85 x 20mm
- N.W: 185g



3.5 inch TFT-LCD screen

VC3

External call stations

- Operating frequency: 2402-2483MHz
- Transmitting power: 16-20dBm
- Camera: 1/4 COMS
- Power adapter: 1/4" Input 100V-240V
- Output 12V/1A
- Working current: 300mA
- Static current <30mA
- Battery capacity: 1350mA
- Standby time: 48 hours
- Colour: Black
- Size: 175 x 105 x 60mm
- N.W: 310g

Indoor Monitor

- Operating current < 250mA
- Screen: 7 inch LCD touch screen
- Sensitivity: -90dBm
- Standby current: 20-30mA/3.7V
- Power adapter: Input AC 100V - 240V
- Output DC5V/1A
- Battery capacity: 2600mA
- Standby time: 72 hours
- Tone: 12 selectable ring tones
- Colour: Black, white
- Size: 100 x 65 x 20mm
- N.W: 130g



7 inch LCD touch screen

Call the GM Techtronics hotline: **0844 824 6690**
or **info@gmtechtronics.co.uk**

GM Techtronics Limited
Unit 17, Paxcroft Farm, Hilperton, Trowbridge, Wiltshire BA14 6JB
www.gmtechtronics.co.uk